

DESOI AirPower S25-2C

No. 17604

Description

The pneumatic reciprocating pump DESOI AirPower S25-2C combines high capacity with compact design. Due to the directly mounted seals on the piston, retensioning is not necessary. The result is a very maintenance-friendly machine.

Material to be used


- 2 component injection resin

Delivery range

carrying frame, 1.5 m suction system Ø 20 mm with suction basket Ø 40 mm: component A: transparent, component B: black, 2 x manometer 0 - 250 bar, material hose connection:
component A: external thread M16x1.5, component B: external thread M14x1.5, return hoses Ø 8 mm: transparent, air connection: air plug NW 7.2, incl. instruction manual

Advantages

- Solid mixing ratio 1 : 1 - no errors by users
- Big material passage - highly viscous material can be used
- No risk of injuries caused by the tension spring seal
- Easy maintenance and repair



1. Pressure regulator with manometer and anti-freeze device

2. Manometer combination and oil lubrication

Technical data

Working pressure - infinitely variable	10 - 100 bar
Delivery rate	max. 7.6 l/min
Air consumption	1 m ³ /min
Air pressure	max. 8 bar
Transmission ratio	1 : 13

Air consumption and delivery rate at 100 bar back pressure (injection pressure)

Air consumption	Delivery rate
75 l/min	0,5 l/min
133 l/min	1 l/min
A283 l/min	2 l/min
391 l/min	3 l/min

Mixing ratio	1 : 1
Weight	20.2 kg
L x W x H	58 x 24 x 46 cm

Accessories

Spare and wear part set DESOI AirPower S25	17600-EVS
Set of tools DESOI AirPower S25	17600-WS